

### Physical Properties

Appearance Liquid with asphalt odor	Color Black	Solids By Weight 54%
Application Temperature 50° F and rising	Flash Point > 212° F	Specific Gravity @ 77° F (25°C) 1.01
Ash 1.3%	Maximum VOC 10 g/l	Weight Per Gallon 8.3-8.7 lbs
Brookfield Viscosity 400-800 cPs		

### Description

DI910 - POURABLE DRIVEWAY CRACK SEALER is ideal for filling cracks 1/4" wide or smaller in blacktop surfaces. It dries to a black, hard rubber seal, providing a crack free surface prior to application of driveway sealers.

### Coverage

One gallon fills 200 - 225 lineal feet of 1/4" x 1/4" cracks

### Surface Preparation

Hose or blow off loose materials, dust and dirt from cracks. Cracks should be damp but free of standing water.

### Application

Mix thoroughly for uniform consistency. Invert container and shake for 1 to 2 minutes.

To use, remove cap and cut tip to 1/8" opening. Place spout in crack. Squeeze container to apply filler in crack. Fill cracks up to 1/4" wide. Filler shrinkage is evident in wide cracks. Fill deep cracks with sand until almost level with pavement. Apply crack filler slightly below pavement surface.

NOTE: Filler applied above surface can cause tracking. Sprinkle sand over filler to help prevent tracking during drying. Plug hole in filler spout when not in use. Coatings should be applied under normal environmental conditions without thinning.

### Precautions

Apply when temperature is at least 50°F and when rain is not likely within 24 hours. Allow filler to dry until firm before covering with driveway sealer. Protect freshly sealed cracks from rain until crack sealer has cured. High humidity or cool temperatures may extend cure time. Do not use as a driveway coating.

Product dries black. Do not thin. Close container after each use.

When transporting this product, be sure the container is secured and the lid is tight. Do not allow container to tumble as this may loosen the lid and allow leakage to occur.

## Cleanup

Clean tools with soap and water immediately after use.

## Caution

CAUTION! Close container after each use. DO NOT TAKE INTERNALLY! Dispose of container and unused contents in accordance with Local, State and Federal regulations.

Use protective measures to avoid contact with eyes and skin. If swallowed, CALL PHYSICIAN IMMEDIATELY! In case of eye contact open eyelids wide and flush immediately with plenty of water for at least 15 minutes. SEEK MEDICAL ATTENTION!

KEEP OUT OF REACH OF CHILDREN!

FOR EXTERIOR USE ONLY.

KEEP FROM FREEZING!

This product contains detectable amounts of chemicals known to the State of California to cause cancer or birth defects, or other reproductive harm.

Employers should obtain a copy of the Material Safety Data Sheet (MSDS) from your supplier or directly from the toll free number or website below.

## Product Sizes

GALLON (10 lb)

## Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**